

ELBA FG AC 2

Elba FG 2 Aluminum complex thickened lubricating grease. It is formulated specifically for the food packaging and processing industry. Elba Aluminum Complex Food Grade grease provides excellent extreme pressure and anti-wear protection and can be used over a wide range of operating temperatures. Aluminum Complex Food Grade grease is also available in grades 1, 2 and 0.

- Recommended for Food and Pharmaceutical industry for incidental contact.
- Provides superior load and rust protection for bearings.
- It works effectively under water borne applications of the food processing industry designed to work effectively in the temperature range of 0°F to 300°F.



General Characteristics		
NLGI Grade	ASTM D 217	2
Worked Penetration 4.	ASTM D 217	265-295
Color	Visual	White
Type of Thickener	-	Aluminum Complex
Viscosity @ 40°C, cSt		64-70
Viscosity @ 100°C, cSt		11.0
Viscosity @ 100°F, SUS	ASTM 445	340-345
Viscosity @ 210°F, SUS		69.0
Four Ball Weld Load, kg	ASTM D 2783	250
Timken Ok Load, lbs	ASTM D 2509	45
Water Washout, wt % loss @ 175 °F	ASTM D 1264	3.5
Pour Point, °F	-	-10
Flash Point, °F (°C)	-	430 (221)

For Technical, Quality or Product Safety Questions Please Contact:

Elba Lubrication Inc., New York / United States of America Phone + 1-631-759-1014 info@elba-lubes.com



