

ELBA LITHOPLEX EP 1,2,3

Elba Lithoplex Grease is Lithium complex base grease formulated with highly refined base oil and specialty additives to meet severe requirements of machinery. The appearance is smooth, adhesive, slightly stringy and BLUE in color. This grease is capable of operations from minus 40°F to 350°F, but has a dropping point of more than 500°F.

Key Features:

- Excellent mechanical stability.
- Good oxidation and corrosion protection.
- Outstanding extreme pressure protection.
- Wide temperature operability (- 40°F to + 350°F).
- Excellent water resistance.

Recommended Applications:

In general, this grease is recommended for extended service in Textile mills, Cement, heavy-duty automotive, trucks, buses, farm tractors, construction equipment, high temp wheel bearings (disc brakes), roller & ball bearings, electric motor bearings, throw-out bearings, universal joints, chassis, fifth wheel, etc. This grease is suitable for medium size high speed bearings. It is robust multi-purpose grease for a wide range of applications.

Customer Benefits:

- Resists thinning or hardening in bearings, thereby minimizing leakage and maintaining extended long life service.
- Specialty additives system minimizes chemical deterioration over extended periods of storage and service.
Protects steel and copper alloy bearings against rust and corrosion.
- Provides effective wear protection for ball joints, drive shafts and other parts subjected to high pressure and shock loading.
- Offers excellent low temperature pump ability and high temperature protection.
- It effectively resists washout and excessive dilution by water, assuring all-weather lubrication.

Products	Lithoplex 1	Lithoplex 1	Lithoplex 1	Test Method
Color	Blue	Blue	Blue	Visual
Texture	Smooth , Tacky	Smooth , Tacky	Smooth , Tacky	Visual
NLGI Grade	1	2	3	ASTM D 217
Worked Penetration	320	280	235	ASTM D-217
Change in Pen After	30 max	30 max	30 max	
Drop Point , °F	500 Min	500 Min	500 Min	ASTM D 2265
Viscosity @ 40 C ,cSt	224	224	22	ASTM D 445
Viscosity @ 100 C ,cSt	17.4	17.4	17.4	
Viscosity @ 100 F ,SUS	1194	1194	1194	
Viscosity @ 210 F ,SUS	89.9	89.9	89.9	-
Type of Thickener	Lithium complex	Lithium complex	Lithium complex	
Weld Load, Kg	315	315	315	ASTM D 2596
Timken OK Load, lbs	60	60	60	ASTM D 2509
Water Spray Off, % wt	-	15 Max	12 Max	ASTM D 4049
Rust Test	Pass	Pass	Pass	ASTM D-1743

For Technical, Quality or Product Safety Questions Please Contact:

Elba Lubrication Inc., New York / United States of America
Phone + 1-631-759-1014
info@elba-lubes.com

The data presented in this medium are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.

ELBALUBES™ | Most Recent Change: 01.07.2022

