

ELBA HT 3 GREASE

ELBA HT 3 Grease is formulated to provide maximum, long lasting protection to bearings, bushings, sliding surfaces and other areas exposed to severe conditions of pounding, moisture, contamination or heavy loads. It is a versatile multi-purpose, extreme pressure and anti-wear grease that protects equipment under the most adverse conditions of excessive pressure; heat/cold and high/low speed applications. ELBA HT 3 Grease is a non-melt grease formulation with high shock protection and corrosion resistance. It is excellent in applications where there is a need to provide extended component life while reducing excessive grease consumption.

Key Features:

- Extreme Pressure Properties
- Non-Melt High Shock Protection
- Rust and Corrosion Resistance

Customer Benefits:

- Protection Under Extremely High Loads and Temperatures
- Will Not Melt, Run or Drip at Any Temperature
- Forms a Seal to Keep Out Damaging Water and Contaminates

Recommended Applications:

Impact Grease is recommended for high-temperature application and provides exceptional lubrication that retards wear and prolongs the service of vital equipment. Typical applications include anti-friction bearings, fifth wheels, king pins, sliding surfaces, conveyors, chassis points, bucket pins, electric motors, couplings, lube systems, open gears, universal joints and several other applications requiring a long-lasting and reliable lubricant.

Typical Performance Data		
NLGI GRADE	ASTM D-217	3
WORKED PENETRATION @ 25° C	ASTM D-217	220 - 250
THICKENER TYPE	DATA	BENTONE
TEXTURE	VISUAL	TACKY
COLOR	VISUAL	GREEN
DROPPING POINT	ASTM D-2265	-
VISCOSITY @ 40° C, CST	ASTM D-445	220.0
VISCOSITY INDEX	ASTM D-2270	-
TIMKEN OK LOAD	ASTM D-2509	60 - 70 LBS
4-BALL WELD LOAD	ASTM D-2596	315 - 400 KG
WATER SPRAY-OFF, % WT	ASTM D-4049	-
COPPER STRIP CORROSION	ASTM D-4048	1B
RUST PREVENTION	ASTM D-1743	-

For Technical, Quality or Product Safety Questions Please Contact:

Elba Lubrication Inc., New York / United States of America
 Phone + 1-631-759-1014
 info@elba-lubes.com

The data presented in this medium are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.

ELBALUBES™ | Most Recent Change: 01.07.2022

