

ELBALUBES EM 2 GREASE

ELBALUBES EM 2 is a premium quality lubricant utilizing a Polyurea thickener system compounded with high quality base stocks to provide excellent protection for electric motor bearings. It is characterized by its state-of-the-art additive technology providing exceptional rust control and oxidation resistance. It's mechanical and shear stability and temperature range durability promote optimal performance under continuous operation.

ELBALUBES EM 2 is designed and tailored specifically for use in electric motor bearings, all types of rolling element bearings and various industrial applications. Always consult with OEM (Original Equipment Manufacturer) for appropriate lubricant viscosity and quality selection.

Product Feature and Benefits:

ELBALUBES EM 2 provides superior performance in applications under high operating temperature, high speed conditions and exhibits exceptional high / low ambient temperature characteristics. It also serves as an effective sealant preventing harmful contaminant ingress.

- Exceptional rust control and oxidation resistance
- Superior performance over wide range of temperatures
- Polyurea Thickener
- Excellent mechanical and shear stability
- Promotes long service life
- Withstands wet operation environment

General Characteristics		
CNLGI Grade	NLGI	2
Color	Visual	Blue
Thickener Type	---	Polyurea
Penetration, 60X worked	ASTM D217	265-295
Dropping Point, min, °C/°F	ASTM D2265	260/500
Rust Test	ASTM D1743	Pass
Copper Corrosion, max rating	ASTM D4048	1B
EMCOR Corrosion, Distilled Water	ASTM D6138	0, 0
EMCOR Corrosion, 10% Syn. Sea Water	ASTM D6138	0, 1
Water Washout, 79°C, % loss	ASTM D1264	3
4 Ball Wear scar diameter, mm, max	ASTM D2266	0.6
Oil Separation, %	ASTM D1742	0.5
High Temp Life, hrs.	ASTM 3336	>750
FAG FE-9 @ 160°C, L50 min, hrs	DIN 51821	>100 hrs.
Base Oil Viscosity @40°C , cSt	ASTM D445	106
Base Oil Viscosity @100°C , cSt	ASTM D445	11.8 – 12.6
Viscosity Index	ASTM D2270	95

For Technical, Quality or Product Safety Questions Please Contact:

Elba Lubrication Inc., New York / United States of America
 Phone + 1-631-759-1014
info@elba-lubes.com

The data presented in this medium are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.

ELBALUBES™ | Most Recent Change: 01.07.2022

