

ELBALUBE FG AIR TOOLS

ELBALUBE FG AIR 22, airline lubricant is formulated specifically for pneumatic tools used in the food service, beverage, and packaging industries. This lubricant meets U.S.D.A. 1998 (H1) guidelines (lubricants with possible incidental food contact). Manufactured in an ISO 21469 Certified facility.

ELBALUBE FG AIR is fortified with a special additive package which gives it excellent oxidation stability and low temperature fluidity. It also contains an emulsifier for superior performance in high moisture environments.



Physical Properties	
Products	ELBALUBE AIR FG-22
ISO Grade	22
Viscosity	
@ 40°C, cSt	22.30
@ 100°C, cSt	4.30
Specific Gravity	0.860
Viscosity Index	96
Pour Point,	
°F(°C)	5 (-15)
Flash Point, °F (°C)	405 (207)
Fire Point, °F (°C)	440 (227)
Four Ball Wear Test, mm	0.54
Foaming Seq. I, II, III	0/0
Copper Strip Corrosion	1A
Rust	Pass

Shelf Life: Product shelf life is 3 years from the date of manufacture, after which the product should be recertified prior to use.

For Technical, Quality or Product Safety Questions Please Contact:

Elba Lubrication Inc., New York / United States of America Phone + 1-631-759-1014 info@elba-lubes.com



